

What is claimed is:

1. A drawer device for holding a container, comprising:

an outside case with a front opening,

an inside case disposed in the outside case to move between  
5 a pulled-out position where the inside case is pulled out from  
the outside case through the front opening and a stored position  
where the inside case is stored in the outside case,

a holder main member disposed in the inside case to move  
between a use position where the holder main member is pulled out  
10 from the inside case and a non-use position where the holder main  
member is stored in the inside case, and

a first locking member pivotally supported on the inside  
case and urged in one direction to engage the holder main member  
to thereby fix the inside case to the holder main member to slide  
15 together, said first locking member releasing the holder main  
member when the holder main member is pulled forward and the  
inside case is at the pulled-out position so that only the holder  
main member can slide further toward the use position.

20 2. A drawer device according to claim 1, further comprising a  
second locking member pivotally supported on the inside case and  
urged in one direction to engage the outside case when the holder  
main member is pulled forward and the inside case is at the  
pulled-out position so that only the holder main member can slide  
25 further toward the use position, said second locking member being  
released from the outside case when the holder main member is  
pushed rearward and the holder main member is at the non-use  
position so that the inside case can slide toward the stored  
position.

30

3. A drawer device according to claim 1, wherein said first and second locking members are formed in substantially a same shape, and includes front ends, rear ends, engaging claws at the front ends, and cam portions at the rear ends.

5

4. A drawer device according to claim 3, wherein said holder main member includes a depression for engaging the engaging claw of the first locking member, and said outside case includes a protrusion for pushing the cam portion of the first locking member to release the engaging claw.

10

5. A drawer device according to claim 3, wherein said outside case has a depression for engaging the engaging claw of the second locking member, and said holder main member includes a projection for pushing the cam portion of the second locking member to release the engaging claw.

15

6. A drawer device according to claim 1, wherein said holder main member includes a holding hole for receiving the container and a movable member rotatably attached to the holder main member for supporting the container when the holder main member is situated at the use position.

20

7. A drawer device according to claim 1, wherein said holder main member has a front face for covering the front opening of the outside case.

25